
Chamber Design and Construction




Chamber design finished in 2010 Delivered to U. of Manitoba Fall of 2010.

The chamber has:

- 4 data ports for up to 200 readout channels.
- 2 HV ports
- 2 gas inlets/outlets
- 12 inch conflat aluminum windows (0.9 mm thick).

Chamber made completely from aluminum except for the knife edges.





Chamber design finished in 2010

Delivered to U. of Manitoba Fall of 2010.

The chamber has:

- 4 data ports for up to 200 readout channels.
- 2 HV ports
- 2 gas inlets/outlets
- 12 inch conflat aluminum windows (0.9 mm thick).

Chamber made completely from aluminum except for the knife edges.




Frame Design and Construction


Chamber frame design was finished in 2012

Received 50 macor wire frames (up to 25 signal and 25 HV) \$30K

Final feature machining planned for early this year at UT shop.


Platinum-Gold thick film wire solder pads on macor to be completed early this year by Hybrid Sources Inc.









The frame mounting structure is designed and pieces will be ordered in the spring.



Two options for frame mounting:

Monolithic exit flange with threaded holes for frame mounting rods
Insert into existing exit window flange







- Signal readout via circuit board traces.

-Single HV connections.

- guide wires to feedthroughs with PMT inspired standoffs and ceramic beads





Target Chamber Assembly Schedule

February 2013:

Have test frame finished by Hybrid Sources and verify measurements.

March 2013:

Complete feature machining at UT shop.

April 2013:

Order remaining parts for frame assembly and feed throughs.

June-July 2013:


Completed Solder pad deposition by Hybrid Sources.

October 2013:



07/01/2013





Design and build readout electronics starting now.